

### **Appearance View**





#### Information:

> Capacity (Cooling)

7,000 BTU 9,000 BTU

➤ Machine Size W×H×D mm

\* 320\*670\*320

Stuffing: 190/392/606

> Remote Control







**Side View** 









**Rear view** 









## **Control Panel**

| Information:      |                                      |
|-------------------|--------------------------------------|
| Control Panel     | Electronic button/<br>Remote Control |
| Mode              | Cooling/Fan/Dry                      |
| Fan               | 2 Level Fan Speed<br>High/Low        |
| Timer             | 24 Hour Timer                        |
| Optional Function | Wifi, Healthy Filter                 |
| Display           | LED Display with Green Letter        |



#### **Features**





**3-in-1 Modes**Cooling/Dry/Fan



**Remote Control & Panel Control** 



**LED Digital Display**Easier to see the setting temperature



24 Hours Timer
Automatic startup/shu

attregular time



Automatic restart (power failure memory)
When the power is off, the phone will start automatically.



2 Level Fan Speed anual swing (High/Low)



**Switchable in Degrees Fahrenheit/Celsius** 



Advanced patented water atomization technology is more efficient, no need frequent drainage.



**Self-Diagnostic Function**Display fault code to quickly determine the fault



**Equipped with casters** convenient to move



WiFi intelligent control (optional)



**Sleeping Mode**Comfortable Sleep, Save Energy



**Easy to Disassemble Washing Filter** 




**Silver Iron Filter (Optional)** 



Multi-functional health filter (optional) Acticarbon&+HEPA

#### **Accessory exhaust pipe installation**








- Rotate the hose pipe inconnector into the hose pipe.
- Insert the hose inconnector into the mac www.bbairtrading.com
- Finished.

1、旋转





3、完成



# 谢 谢!

